



Aero BTA Riser - Installation Instructions

WARNING: Do not allow threadlocker (e.g. Loctite) to contact the riser, this will void the warranty, as it will weaken the base materials and lead to product failure. If using threadlocker, apply after inserting bolts and avoid all contact with the riser.

- 1) Remove any existing riser(s) or spacer(s).
- 2) *Optional* - Insert activated Apple AirTag into compartment.
- 3) Orient riser with the rounder section facing forward, and the thinner edge to the rear.
- 4) Torque included mounting bolts to 4Nm (35 in-lbs) with hex driver,
DO NOT exceed 5Nm (45 in-lbs).
- 5) Install cage (or desired accessory) onto riser, by placing two M5 bolts (*not included*) of sufficient length through cage and into riser inserts.
- 6) Ride and enjoy!
- 7) *Removal* - AirTag may be removed by firmly tapping one end of the riser onto a firm surface, until AirTag has moved enough to be removed by hand.

-Got a product idea? Let us know, you'll get a discount coupon or a free product if we make it!-

Warranty Information: This product is warranted to be free from defects in materials and workmanship for a period of six months from the date of original purchase. During this period, the manufacturer will repair or replace, at its discretion, any defective product. Contact Support@30mmDesign.com for any warranty claims or technical assistance.